


# Crosby® Trawlex® Chain


All breaking loads are in metric tonnes. To maximize the benefits of the improved strength of the chain, only use compatible Trawlex® fittings.



## Crosby Trawlex® Short Link Chain

Model	Stock No.	Chain Dia. (mm)	Link Dimensions (mm)		Breaking Load (t)		Weight (kg.)	Standard Length (m)
			Pitch	Width	Trawlex®	Grade 80		
TRAW-SL	2781650	10	30	14	15.5	12	2.2	200
TRAW-SL	2781652	13	39	18.1	26.5	20	3.61	150
TRAW-SL	2781635	16	48	22.4	41	30	5.41	110
TRAW-SL	2781644	19	57	26.6	57	45	7.81	75


## Crosby Trawlex® Mid Link Chain



Model	Stock No.	Chain Dia. (mm)	Link Dimensions (mm)		Breaking Load (t)		Weight (kg.)	Standard Length (m)
			Pitch	Width	Trawlex®	Grade 80		
TRAW-ML	2784579	10	40	15	15.5	12	1.85	250
TRAW-ML	2784561	13	52	19.5	26.5	20	3.21	150
TRAW-ML	2784507	16	64	22.4	41	30	4.86	110
TRAW-ML	2784516	16	64	22.4	41	30	4.86	600
TRAW-ML	2781653	16	64	22.4	41	30	4.86	110
TRAW-ML	2784534	16	64	22.4	41	30	4.86	600
TRAW-ML	2784570	19	76	27	57	45	6.92	75
TRAW-ML	2784525	19	76	27	57	45	6.92	300
TRAW-ML	2781662	19	76	27	57	45	6.92	75
TRAW-ML	2784543	19	76	27	57	45	6.92	300
TRAW-ML	2781671	22	86	26	75	60	9.24	60
TRAW-ML	2784552	22	86	26	75	60	9.24	110
TRAW-ML	2781680	26	92	30	95	85	13.66	50

 Denotes Profile Chain™

## Crosby Trawlex® Long Link Chain



Model	Stock No.	Chain Dia. (mm)	Link Dimensions (mm)		Breaking Load (t)		Weight (kg.)	Standard Length (m)
			Pitch	Width	Trawlex®	Grade 80		
TRAW-LL	2781699	9	53	15	12.5	10	1.36	200
TRAW-LL	2781706	11	63	18	18.5	15	2.03	150
TRAW-LL	2781715	13	80	22	26.5	20	2.83	150
TRAW-LL	2781720	13	80	22	26.5	20	2.83	600
TRAW-LL	2784339	16	100	24.5	40	30	4.34	100
TRAW-LL	2784348	16	100	24.5	40	30	4.34	600
TRAW-LL	2781724	16	100	24.5	40	30	4.34	100
TRAW-LL	2784320	16	100	24.5	40	30	4.34	600
TRAW-LL	2784357	19	100	25	57	45	6.31	108
TRAW-LL	2781733	19	100	25	57	45	6.31	108
TRAW-LL	2781742	22	120	35.5	70	60	8.74	70
TRAW-LL	2781751	28	150	46	105	95	14.41	50

 Denotes Profile Chain™